



Fiber Hole Diameter "D1" (microns)	"D1" Size Tolerance (microns)	Concentricity "C1" (microns)
128-149	+5/-0	< 10
150-249	+10/-0	< 10
250-1499	+15/-0	< 15
1500-1700	+25/-0	< 25

**CUSTOMER DRAWING
FOR REFERENCE ONLY**

Notes:

- 1) Ferrule material is stainless steel
coupling nut is nickel plated brass
rear body material is Zamac cast
collet material is liquid crystal polymer
- 2) Part number is "3003-XXXX-YYYY" where -XXXX is hole size in microns and -YYYY is collet size in microns

i.e. hole size of 640um and collet size of 1040um
the part number is 3003-0640-1040
- 3) Connector comes with 3mm boot and dust cap



88 Bee Brook Road
Washington Depot, CT 06794
Phone: 860-868-0081
sales@berkshirephotonics.com
www.berkshirephotonics.com

Confidentiality Notice

This document is proprietary to Berkshire Photonics and any reproduction, disclosure, or use thereof is expressly prohibited without the written permission of Berkshire Photonics

Dimension Millimeters	SCALE NTS	SIZE A
DRAWN M. Windebank	APPROVED J. Miller	DATE 4/28/16
Description Damage Resistant Stainless Steel SMA Connector, Fiber Grip		
DWG NO. 3003-XXXX-YYYY	REV A	SHEET 1 OF 1